

Features		Navigation Remote Controller	Madoka Remote Controller	Daikin One+ Smart Thermostat	DKN Cloud Wi-Fi Adaptor	DKN Plus Interface (adaptor only)	DKN Plus Interface (w/Tstat)	Adaptive Touch Controller			
		BRC1E73	BRC1H71W	DTST-ONE-ADA-A	AZAI6WSCDKA	AZAI6WSPDKC		BACRC-T-P01	BACRC-TH-P01	BACRC-THO-P01	BACRC-THOC-P01
Protocol	P1P2 or S21	P1P2	P1P2	P1P2/S21	P1P2	P1P2/S21	P1P2/S21	P1P2	P1P2	P1P2	P1P2
Display and Indicator	LCD non-color display	x	x				Depends on Tstat				
	Colorful display			x			Depends on Tstat	x	x	x	x
	Touchscreen display			x			Depends on Tstat	x	x	x	x
	Customizable display	x	x				Depends on Tstat				
	Screensaver			x			Depends on Tstat	x	x	x	x
	ON/Off LED light	x	x (Dimmable/Off)				Depends on Tstat				
	Colorful LED light to indicate controller status		x				Depends on Tstat				
	Colorful Display background to indicate controller status						Depends on Tstat	x	x	x	x
Sensing	Colorful LED light to indicate active heating/cooling status			x			Depends on Tstat				
	Built-in temperature sensor	x	x	x			Depends on Tstat	x	x	x	x
	Built-in humidity sensor			x			Depends on Tstat	x (external only)	x	x	x
	Built-in occupancy sensor						Depends on Tstat	x (external only)	x (external only)	x	x
	Built-in CO ₂ sensor						Depends on Tstat	x (external only)	x (external only)	x (external only)	x
Basic Indoor Unit Control	VOC sensor			x (with IAQ sensor only)							
	On/Off	x	x	x	x	x	x	x	x	x	x
	Mode - Cool/Heat	x	x	x	x	x	x	x	x	x	x
	Mode - Auto	x	x	x	x	x	x	x	x	x	x
	Mode - Fan	x	x		x	x	x	x	x	x	x
	Mode - Dry (indoor unit logic)	x	x		x	x	x	x	x	x	x
	Set-point	x	x	x	x	x	x	x	x	x	x
	Fan speed	x	x	x	x	x	x	x	x	x	x
	Louver control (positions/swing/fixed/auto)	x	x	x	x (vertical only)	x (vertical only)	x (vertical only)	x	x	x	x
	Error code with plain text	x	x	x	x	x	x	x	x	x	x
	Natural language alarm			x	x	x	x				
Indoor Unit Setting (for FXFQ & FXUQ only)	Changeover master/follower indication	x	x	x	x	x	x	x	x	x	x
	Individual louver position for FXFQ and FXUQ	x	x					x	x	x	x
	Draft prevention	x	x	x				x	x	x	x
	Auto filter cleaning	x	x					x	x	x	x
	Auto-setback and Auto-off	x	x					x	x	x	x

Features		Navigation Remote Controller	Madoka Remote Controller	Daikin One+ Smart Thermostat	DKN Cloud Wi-Fi Adaptor	DKN Plus Interface (adaptor only)	DKN Plus Interface (w/Tstat)	Adaptive Touch Controller			
		BRC1E73	BRC1H71W	DTST-ONE-ADA-A	AZAI6WSCDKA	AZAI6WSPDKC		BACRC-T-P01	BACRC-TH-P01	BACRC-THO-P01	BACRC-THOC-P01
Advanced Control	Autochangeover with guard timer	x	x	x	x	x	x	x	x	x	x
	Set-point range limitation	x	x	x			Depends on Tstat	x	x	x	x
	Dual set-point for H/C	x	x	x	x	x	x	x	x	x	x
	Unoccupied set-point (Setback control)	x	x	x			Depends on Tstat	x	x	x	x
	Minimum set-point differential	x	x	x			Depends on Tstat	x	x	x	x
	Individual fan speed for cooling and heating	x	x	x			Depends on Tstat				
	Schedule	x		x	x	x	x	x	x	x	x
	Humidity control with humidity set-point			x (Dehum with overcooling logic)			Depends on Tstat	X (External)	x (configurable hum control)	x (configurable hum control)	x (configurable hum control)
	CO2 control with setpoint						Depends on Tstat	X (External)	X (External)	X (External)	x
	Configurable occupancy sensor logic						Depends on Tstat	X (External)	X (External)	x	x
Auxiliary Heater Control	Secondary heater	x (with KRP1C only)	x (with KRP1C only)	x	x (with KRP1C only)	x	x	x	x	x	x
	Primary heater			x			Depends on Tstat	x	x	x	x
	Emergency heater			x		x	x	x	x	x	x
	Alternative Heat							x	x	x	x
	Priority cooling logic							x	x	x	x
	Back up heat control with KPR1C board	x	x		x	x					
Integration Option	Cloud API			x		x	x				
	BACnet™ MS/TP					x	x	x	x	x	x
	Modbus®				x	x	x				
	Third-party thermostat					x	x				
Connectivity	Built-in Bluetooth® communication		x (Setup only)	x (Setup only)	x (Setup only)	x (Setup only)	x (Setup only)				
	Built-in SubGHz communication			x							
	Bluetooth® configuration app		x		x	x	x				
	Smartphone control via Wi-Fi			x	x	x	x				
	Voice Control with Amazon Alexa and Google Assistant			x	x	x	x				
	Dealer Web portal			x			Depends on Tstat				
	Weather forecast information			x			Depends on Tstat				
	Geo-fencing			x			Depends on Tstat				
Over-the-air (OTA) Software update			x	x	x	x					
Regional Support	Support Multiple Languages (EN, FR, ES)	x	x	x	x	x	x				
	Date and Time with Automatic DST	x	x	x	x	x	x	x	x	x	x
	F/C conversion	x	x	x	x	x	x	x	x	x	x

FOR MORE INFORMATION ON DAIKIN REMOTE CONTROLLERS, VISIT WWW.DAIKINAC.COM