

Rated Capacity	IDU	SkyAir FAQ Wall Mount – Heat Pump & Cooling Only								SkyAir FBQ HSP Ducted – Heat Pump & Cooling Only						SkyAir FCQ Round Flow Sensing Ceiling Cassette – Heat Pump & Cooling Only					SkyAir FHQ Ceiling Suspended – Heat Pump & Cooling Only (FHQ efficiencies rated to SEER/EER/HSPF)				
		FAQ18TAVJU	FAQ24TAVJU	FBQ18TBVJU	FBQ24TBVJU	FBQ30TBVJU	FBQ36TBVJU	FBQ42TBVJU	FBQ48TBVJU	FCQ18AAVJU	FCQ24AAVJU	FCQ30AAVJU	FCQ36AAVJU	FCQ42AAVJU	FCQ48AAVJU	FHQ18PVJU	FHQ24PVJU	FHQ30PVJU	FHQ36MVJU	FHQ42MVJU					
		ODU Cooling Only	RZR18TBVJUA	RZR24TBVJUA	RZR18TBVJUA	RZR24TBVJUA	RZR30TBVJUA	RZR36TBVJUA	RZR42TBVJUA	RZR48TBVJUA	RZR18TBVJUA	RZR24TBVJUA	RZR30TBVJUA	RZR36TBVJUA	RZR42TBVJUA	RZR48TBVJUA	RZR18TAVJUA	RZR24TAVJUA	RZR30TAVJUA	RZR36TAVJUA	RZR42TAVJUA				
ODU Heat Pump	RZQ18TBVJUA	RZQ24TBVJUA	RZQ18TBVJUA	RZQ24TBVJUA	RZQ30TBVJUA	RZQ36TBVJUA	RZQ42TBVJUA	RZQ48TBVJUA	RZQ18TBVJUA	RZQ24TBVJUA	RZQ30TBVJUA	RZQ36TBVJUA	RZQ42TBVJUA	RZQ48TBVJUA	RZQ18TAVJUA	RZQ24TAVJUA	RZQ30TAVJUA	RZQ36TAVJUA	RZQ42TAVJUA						
Cooling	18,000	24,000	17,700	23,400	28,400	35,000	40,000	46,500	18,000	24,000	30,000	36,000	42,000	48,000	18,000	24,000	30,000	36,000	40,500						
Heating	20,000	27,000	20,600	27,400	34,800	40,000	47,000	54,000	20,000	27,000	34,000	40,000	47,000	54,000	20,000	27,000	34,000	40,000	40,000						
SEER2	16.9	17.3	15.5	15.4	16.5	16.9	15.6	15.3	18.5	18.6	21	20	18.9	18	16.3	16.6	16	14	14.0						
EER2	11.9	10.2	12.5	10.5	12.2	11.7	10.3	8.3	13	12	13	12.1	10.3	8.2	12.9	11.3	10.5	9.5	8.8						
HSPF2 (Heat Pump)	7.6	7.8	8.5	9.3	8.9	8.8	9.5	9.3	9.2	9.1	10.1	10	10.2	10.3	9.3	9.3	8.4	8.2	8.2						
AHRI Cooling Only #	211635147	211635148	211635149	211635150	211635151	211635152	211635153	211635145	211635139	211635140	211635141	211635142	211635143	211635144	205707040	205707041	205707042	205707043	205707044						
AHRI Heat Pump #	211635168	211635169	211635170	211635171	211635172	211635173	211635174	211635175	211635162	211635163	211635164	211635165	211635166	211635167	205801308	205706998	205706999	205707000	205707001						
MOP IDU	15								15																
MOP ODU	20								20						20				35						
Line Size (in.) (mm)	3/8 x 5/8 (9.5 x 15.9)								3/8 x 5/8 (9.5 x 15.9)						3/8 x 5/8 (9.5 x 15.9)				3/8 x 5/8 (9.5 x 15.9)						
Max Length (ft.) (m)	164 (50)			164 (50)				230 (70)	164 (50)					230 (70)	164 (50)				230 (70)						
Max Height (ft.) (m)	98.4 (30)							98.4 (30)						98.4 (30)					98.4 (30)						
Chargeless (ft.) (m)	15 (4.5)							15 (4.5)						15 (4.5)					15 (4.5)						
Add'l Charge (lb./ft.) (kg/m)	0.036 (0.0535)							0.036 (0.0535)						0.036 (0.0535)					0.036 (0.0535)						
Cooling	23 - 122°F (-5 - 50°C)							23 - 122°F (-5 - 50°C)						23 - 122°F (-5 - 50°C)					23 - 122°F (-5 - 50°C)						
Cooling with Air Direction Adjustment Grille	0 - 122°F (-17.8 - 50°C)							0 - 122°F (-17.8 - 50°C)						0 - 122°F (-17.8 - 50°C)					0 - 122°F (-17.8 - 50°C)						
Air Direction Adjust. Grille	KPW5G112							KPW5F80 x 2	KPW5G112					KPW5F80 x 2	KPW5G112				KPW5F80 x 2						
Heating	-4 - 60°F (-20 - 15.5°C)							-4 - 60°F (-20 - 15.5°C)						-4 - 60°F (-20 - 15.5°C)					-4 - 60°F (-20 - 15.5°C)						
Drain Pan Heater	KEHJ5A160E							KEHJ5A160E						KEHJ5A160E					KEHJ5A160E						

Rated Capacity	IDU	SkyAir FTQ Air Handling Unit Heat Pump & Cooling Only						NV Series HP & Cooling Only		LV 30/36 – Cooling Only	
		FTQ18 TAVJUD/A	FTQ24 TAVJUD/A	FTQ30 TAVJUD/A	FTQ36 TAVJUD/A	FTQ42 TAVJUD/A	FTQ48 TAVJUD/A	FTX30NVJU	FTX36NVJU	FTXS30LVJU	FTXS36LVJU
		ODU Cooling Only	RZR18TBVJUA	RZR24TBVJUA	RZR30TBVJUA	RZR36TBVJUA	RZR42TBVJUA	RK30NMVJUA	RK36NMVJUA	RKS30LVJU	RKS36LVJU
ODU Heat Pump	RZQ18TBVJUA	RZQ24TBVJUA	RZQ30TBVJUA	RZQ36TBVJUA	RZQ42TBVJUA	RZQ48TBVJUA	RX30NMVJUA	RX36NMVJUA	-	-	
Cooling	17,200	23,400	29,500	35,000	40,500	47,000	31,400 (10,200 - 31,400)	34,400 (10,200 - 34,400)	30,000 (10,200 - 30,000)	36,000 (10,200 - 36,000)	
Heating	20,000	27,400	34,000	40,000	47,000	54,000	34,800 (10,200 - 34,800)	36,000 (10,200 - 36,000)	-	-	
SEER2	15.6	16.2	15.6	16.4	16	15.3	17.5	15.9	19.3	17.9	
EER2	11.7	9.9	11.9	11.2	10.6	9.1	9.85	9.1	10.71	8.37	
HSPF2 (Heat Pump)	8.1	8.7	9.1	8.8	9.2	8.8	9.3	9.2	-	-	
AHRI Cooling Only #	211635154	211635155	211635156	211635157	211635158	211635146	205663340	205663341	5433345	5433347	
AHRI Heatpump #	211635176	211635177	211635180	211635181	211635178	211635179	205663347	205663348	-	-	
MOP IDU							15				
MOP ODU	20						35			20	
Line Size (in.) (mm)							3/8 x 5/8 (9.5 x 15.9)			3/8 x 5/8 (9.5 x 15.9)	
Max Length (ft.) (m)		164 (50)					230 (70)			98.4 (30)	
Max Height (ft.) (m)							98.4 (30)			65.625 (20)	
Chargeless (ft.) (m)							15 (4.5)			32.8 (10)	
Add'l Charge	(0.036 x piping length) + .10 lb./ft. (0.0535 x piping length) + 0.05 kg/m						(0.036 x piping length) + 0.71 lb./ft. (0.0535 x piping length) + 0.32 kg/m			(0.036 x piping length) + 1.05 lb./ft. (0.0535 x piping length) + 0.48 kg/m	
Cooling							23 - 122°F (-5 - 50°C)			50 - 115°F (10 - 46°C)	
Cooling with Jumper							-			50 - 115°F (10 - 46°C)	
Cooling with Air Direction Adjustment Grille							0 - 122°F (-17.8 - 50°C)			0 - 115°F (-17.8 - 46°C)	
Air Direction Adjust. Grille		KPW5G112					KPW5F80 x 2			KPW063B4	
Heating							-4 - 60°F (-20 - 15.5°C)			5 - 65°F (-15 - 18°C)	
Drain Pan Heater							KEHJ5A160E			KEH063A4E / KEH063A4EA	

* NV Series and LV 30/36 efficiencies rated to SEER/EER/HSPF

** 22 - 115°F (-30 - 60°C) possible on cooling only model with additional dipswitch setting

SkyAir Controls (Required with Unit)	
2-Wire = (Non-shielded, 2-Conductor, Stranded, AWG-18)	
BRC1E73	Wired Navigation Remote Controller
AZA16WSPDKC	DKN Plus Interface
AZA16WSCDKA	DKN Wi-Fi Adaptor
DTST-ONE-ADA-A	Daikin One Plus Smart Thermostat
BRC1H71W	Daikin Madoka Remote Controller
Single Zone and Multi-Zone Controls	
4-Wire = (Non-shielded, 4-conductor, stranded, AWG-14)	
For CDXS, CTXS, CTX, FDXS, FTK, FTX, FTXG, FTXM**, FTXR, FTXS, FVXS	
BRC944B2-A08	Wired Remote Controller
DTST-ONE-ADA-A*	Daikin One Plus Smart Thermostat
AZA16WSCDKB*	DKN Residential Wi-Fi adaptor
AZA16WSPDKC*	DKN Plus Interface
Wired Controller Adaptor for AURORA Wall Mounts	
KRP067A41	Size: 09 / 12
KRP980B2	Size: 15
For FFQ Cassette & FDMQ Ducted Concealed (Required with Unit)	
BRC1H71W	Madoka Remote Controller
BRC1E73	Wired Navigation Remote Controller
AZA16WSCDKA	DKN Wi-Fi Adaptor
DTST-ONE-ADA-A	Daikin One+ Smart Thermostat
AZA16WSPDKC	DKN Plus Interface
BRC082A42W/S	Wireless Remote Controller - FFQ
BRC082A43	Wireless Remote Controller - FDMQ

*Not compatible with FTK_A or FTX_A 19 Series units
**Requires KER087A41 for any optional controller

COMFORTABLE LIMITED WARRANTY* PROTECTION

Single and Multi-Zone Systems*		SkyAir™†
NV Series ^{††} , Daikin C/IRRA, 17 Series, LV 30/36 ^{††}	19 Series, Daikin AURORA, Daikin EMURA, LV Series, FDMQ, Daikin ATMOSPHERA, VISTA, RMXS/MXS Series	All products

* Complete warranty details available from your local dealer or at www.daikincomfort.com. To receive the 10-Year or 12-Year Parts Limited Warranties, online registration must be completed within 60 days of installation. Online registration and some of the additional requirements are not required in California or Québec.
† If product installed in a commercial application, limited warranty period is 5 years. The duration of warranty coverages in Texas differs in some cases.
†† Limited warranty, registration not required for residential and commercial installations.



ADDITIONAL INFORMATION
Before purchasing this appliance, read important information about its estimated annual energy consumption, yearly operating cost, or energy efficiency rating that is available from your retailer.

DAIKIN

DAIKIN SINGLE AND MULTI-ZONE SYSTEMS

The units detailed in this flyer meet the 2023 U.S. Department of Energy Regional Standards for the Northern and Southeast regions.

Product Class	N U.S. Region Standard Levels	SE U.S. Region Standard Levels
Split-System ACs	SEER = 14 SEER2 = 13.4	SEER = 15 (Cooling capacity less than 45,000 Btu/h) SEER = 14.5 (Cooling capacity equal to or greater than 45,000 Btu/h) SEER2 = 14.3 (Cooling capacity less than 45,000 Btu/h) SEER2 = 13.8 (Cooling capacity equal to or greater than 45,000 Btu/h)
Split-System HPs*	14.3 SEER2 7.5 HSPF2	14.3 SEER2 7.5 HSPF2

* All Heat pumps with SEER/EER/HSPF ratings in this document can continue to be sold and installed in DOE North, Southeast regions. Some units in this document comply with U.S. DOE Regional Standards for the Southwest Region. All units in this document are eligible to be sold in Canada

SINGLE ZONE SYSTEMS

	17 Series – Heat Pump and Cooling Only				19 Series – Heat Pump and Cooling Only			
IDU Cooling Only	FTK09AXVJU	FTK12AXVJU	FTK18AXVJU	FTK24AXVJU	FTK09AXVJU	FTK12AXVJU	FTK18AXVJU	FTK24AXVJU
IDU Heat Pump	FTX09AXVJU	FTX12AXVJU	FTX18AXVJU	FTX24AXVJU	FTX09AXVJU	FTX12AXVJU	FTX18AXVJU	FTX24AXVJU
ODU Cooling Only	RKB09AXVJU	RKB12AXVJU	RKB18AXVJU	RKB24AXVJU	RK09AXVJU	RK12AXVJU	RK18AXVJU	RK24AXVJU
ODU Heat Pump	RXB09AXVJU	RXB12AXVJU	RXB18AXVJU	RXB24AXVJU	RX09AXVJU	RX12AXVJU	RX18AXVJU	RX24AXVJU
Cooling Capacity Rated (Min - Max) Btu/hr	8,800 (4,400 - 10,200)	11,000 (4,400 - 16,200)	18,000 (4,300 - 21,200)	21,200 (6,000 - 22,200)	8,900 (4,400 - 10,200)	10,900 (4,400 - 13,300)	18,000 (5,500 - 20,000)	21,200 (5,500 - 24,000)
Heating Capacity Rated (Min - Max) Btu/hr	9,400 (4,400 - 13,600)	11,300 (4,400 - 16,200)	17,900 (4,000 - 22,500)	21,200 (4,100 - 27,300)	9,400 (4,400 - 13,000)	11,300 (4,400 - 16,400)	18,000 (5,500 - 24,000)	23,600 (5,800 - 27,600)
SEER	17				19		18.5	
EER	11	8.5	10.5	11	12.5			
HSPF (Heat Pumps)	9				10		9	
AHRI Cooling Only #	10578900	10571502	10571503	10571504	205782844	205782849	205782850	205782851
AHRI Heat Pump #	10578901	10574119	10574896	10575515	205782845	205782846	205782847	205782848
MOP	15		20		15		20	
Line Size (in.) (mm)	1/4 x 3/8 (6.4 x 9.5)		1/4 x 1/2 (6.4 x 12.7)	1/4 x 5/8 (6.4 x 15.9)	1/4 x 3/8 (6.4 x 9.5)		1/4 x 1/2 (6.4 x 12.7)	1/4 x 5/8 (6.4 x 15.9)
Max Length (ft.) (m)	65.625 (20)		98.4 (30)		65.625 (20)		98.4 (30)	
Max Height (ft.) (m)	32.8 (10)				49.25 (15)		65.625 (20)	
Chargeless (ft.) (m)	24.6 (7.5)				32.8 (10)			
Add'l Charge (oz./ft.) (g/m)	0.21 (20)				0.21 (20)			
Cooling Operating Range	50 - 115°F (10 - 46°C)				50 - 115°F (10 - 46°C)			
Cooling Range with Jumper	-				5 - 115°F (-15 - 46°C)			
Cooling Range with Air Direction Adjustment Grille	-				-4 - 115°F (-20 - 46°C)			
Air Direction Adjustment Grille	-				KPW937F4		KPW063B4E	
Heating Operating Range	5 - 65°F (-15 - 18°C)				5 - 65°F (-15 - 18°C)			
Drain Pan Heater	-				KEH067A41E / KEH067A41EA		KEH063A4EA	

	Daikin <i>AURORA</i> – Heat Pump											VISTA – Heat Pump				Daikin <i>EMURA</i> – Heat Pump			LV Series – Heat Pump																																																																			
	IDU	FTX09NMVJUA	FTX12NMVJUA	FTX15NMVJUA	FTX18UVJU	FTX24UVJU	FVXS09NVJU	FVXS12NVJU	FVXS15NVJU	FDMQ12RVJU	FDMQ18RVJU	FDMQ24RVJU	FFQ09Q2VJU	FFQ12Q2VJU	FFQ15Q2VJU	FFQ18Q2VJU	FTXR09TVJUW/S	FTXR12TVJUW/S	FTXR18TVJUW/S	FTXS09LVJU	FTXS12LVJU	FTXS15LVJU	FTXS18LVJU	FTXS24LVJU	FDXS09LVJU	FDXS12LVJU																																																												
Rated Capacity (Min - Max)	ODU	RXL09QMVJUA	RXL12QMVJU9A	RXL15QMVJUA	RXL18UMVJUA	RXL24UMVJUA	RXL09QMVJUA	RXL12QMVJU9A	RXL15QMVJUA	RXL12QMVJU9A	RXL18UMVJUA	RXL24UMVJUA	RX09RMVJU9A	RX12RMVJU9A	RX15RMVJU9A	RX18RMVJU9A	RX09RMVJU9A	RX12RMVJU9A	RX18RMVJU9A	RXS09LVJU	RXS12LVJU	RXS15LVJU	RXS18LVJU	RXS24LVJU	RXS09LVJU	RXS12LVJU																																																												
Cooling		9,000 (4,400 – 10,900)	10,600 (4,400 – 13,300)	15,000 (5,800 – 18,400)	18,000 (9,000-21,600)	21,200 (9,000-25,800)	9,000 (4,400 – 10,200)	10,200 (4,400 – 12,300)	15,000 (5,800 – 17,100)	10,800 (6,500 - 13,200)	17,600 (9,000 - 20,200)	21,200 (9,000 - 24,000)	9,100 (4,600 – 11,000)	10,800 (4,600 – 13,300)	14,400 (5,100 – 16,200)	17,400 (5,100 – 18,800)	9,000 (4,500 – 10,600)	12,000 (4,500 – 12,800)	18,000 (5,100 – 18,500)	9,000 (4,400 – 9,000)	12,000 (4,800 – 12,000)	15,000 (5,800 – 15,000)	18,000 (5,800 – 18,000)	21,500 (7,800 – 21,500)	8,500 (4,400 – 8,500)	11,500 (4,800 – 11,500)																																																												
Heating		10,900 (4,400 – 16,000)	13,400 (4,400 – 18,800)	18,300 (5,800 – 24,600)	21,600 (9,000-28,000)	24,000 (9,000-32,000)	10,100 (4,400 - 14,300)	13,000 (4,400 - 17,100)	18,300 (5,800 – 24,000)	13,600 (6,300 - 17,000)	21,600 (9,000 - 25,000)	24,000 (9,000 - 27,600)	10,000 (4,600 – 14,000)	13,500 (4,600 – 16,800)	16,200 (5,200 – 16,300)	21,600 (5,400 – 21,800)	10,000 (4,100 – 14,600)	13,500 (4,100 – 15,800)	20,000 (5,800 – 21,200)	12,000 (4,400 – 12,000)	14,400 (4,800 – 14,400)	18,000 (5,800 – 18,000)	21,600 (5,800 – 21,600)	25,400 (7,800 – 25,400)	10,000 (4,400 – 10,000)	11,500 (4,800 – 11,500)																																																												
SEER		20					20.3					20					18					17					14.5					24.5					23					20.6					20.3					20					15.1					15.5																								
EER		12.5					13					12.5					12.5					11					9.6					15.3					12.8					14.4					12.7					12.5					11.2					9.1																								
HSPF		12.5					10.3					11.7					11.3					10.8					10.3					10					11.7					11.2					11					10.1					9.3					9.8					12.5					11.6					10.6					10.4				
AHRI #	AHRI	207776277	207776278	208136394	205663342	205663345	207776280	207776281	205663350	207776282	205663343	205663344	207776283	207776284	205663346	205663362	207776285 / 207776286	207776288 / 207776289	205663363 / 205663364	5265753	5265755	5265756	5265757	5265758	5265759	5265777	5265840																																																											
MOP		15					20					15					20					1515					15					20					15																																																	
Line Size (in.) (mm)		1/4 x 3/8 (6.4 x 9.5)			1/4 x 1/2 (6.4 x 12.7)			1/4 x 5/8 (6.4 x 15.9)			1/4 x 3/8 (6.4 x 9.5)			1/4 x 1/2 (6.4 x 12.7)			1/4 x 5/8 (6.4 x 15.9)			1/4 x 3/8 (6.4 x 9.5)			1/4 x 1/2 (6.4 x 12.7)			1/4 x 3/8 (6.4 x 9.5)			1/4 x 1/2 (6.4 x 12.7)			1/4 x 5/8 (6.4 x 15.9)			1/4 x 3/8 (6.4 x 9.5)																																																			
Max Length (ft.) (m)		65.625 (20)					98.4 (30)					65.625 (20)					98.4 (30)					65.625 (20)					98.4 (30)					65.625 (20)					98.4 (30)					65.625 (20)																																												
Max Height (ft.) (m)		49.25 (15)					65.625 (20)					49.25 (15)					65.625 (20)					49.25 (15)					65.625 (20)					49.25 (15)					65.625 (20)					49.25 (15)																																												
Chargeless (ft.) (m)							32.8 (10)										32.8 (10)										32.8 (10)										32.8 (10)																																																	
Add'l Charge (oz./ft.) (g/m)		0.21 (20)					0.32 (30)					0.21 (20)					0.32 (30)					0.21 (20)					0.32 (30)					0.21 (20)					0.32 (30)					0.21 (20)																																												
Operating Range	Cooling											50 - 115°F (10 - 46°C)																				50 - 115°F (10 - 46°C)																																																						
	Cooling with Jumper											5 - 115°F (-15 - 46°C)																				14 - 115°F (-10 - 46°C)																																																						
	Cooling with Air Direction Adjustment Grille											-4 - 115°F (-20 - 46°C)																				-4 - 115°F (-20 - 46°C)																																																						
	Air Direction Adjust. Grille	KPW937F4					KPW063B4					KPW937F4					KPW063B4					KPW937F4					KPW063B4					KPW937F4					KPW063B4					KPW945B4					KPW937C4																																							
	Heating Operation Range	-13 - 60°F (-25 - 15.5°C)					-13 - 65°F (-25 - 18.3°C)					-13 - 60°F (-25 - 15.5°C)*					-13 - 65°F (-25 - 18.3°C)					5 - 65°F (-15 - 18°C)					5 - 65°F (-15 - 18°C)					5 - 65°F (-15 - 18°C)					5 - 65°F (-15 - 18°C)																																																	
	Drain Pan Heater	KEH067A41EA			KEH063A4E / KEH063A4EA			KEH067A41EA			KEH063A4E(A)			KEH067A41EA			KEH063A4E / KEH063A4EA			KEH067A41EA			KEH063A4E(A)			KEH067A41EA			KEH063A4E(A)			KEH041A41			KEH041A42			KEH041A43			KEH041A41																																													

*FTX12NMVJURXL12QMVJU9 and FVXS12NVJURXL12QMVJU9 have a heating operation range of -13 - 65°F (-25 - 18.3°C) WB.

	FDMQ Ducted Concealed – Heat Pump					Daikin <i>ATMOSPHERA</i> ** – R-32 Heat Pump				Multi-Zone Indoor Unit	Nominal Capacity	Dimensions (H x W x D) (in.) (mm)	Line Size (in.) (mm)	Weight (lb.) (kg)																						
	IDU	FDMQ09RVJU	FDMQ12RVJU	FDMQ15RVJU	FDMQ18RVJU	FDMQ24RVJU	FTMX09VVJU	FTXM12VVJU	FTXM18VVJU						FTXM24VVJU																					
Rated Capacity (Min - Max)	ODU	RX09RMVJU9A	RX12RMVJU9A	RX15RMVJU9A	RX18RMVJU9A	RX24RMVJU9A	RXM09VVJU	RXM12VVJU	RXM18VVJU	RXM24VVJU																										
Cooling		9,000 (3,900 - 10,700)	10,800 (4,000 - 12,800)	14,400 (5,100 - 17,400)	17,600 (5,100 - 19,600)	21,800 (5,500 - 24,000)	9,000 (4,400 - 12,500)	12,000 (4,800 - 16,000)	18,000 (9,000 - 22,000)	21,600 (9,000 - 26,000)																										
Heating		10,900 (3,900 - 14,000)	13,600 (3,900 - 16,100)	18,000 (5,600 - 18,500)	21,600 (5,700 - 23,000)	24,000 (6,400 - 27,600)	11,000 (4,400 - 19,500)	13,600 (4,800 - 22,600)	21,600 (9,000 - 30,200)	24,000 (9,000 - 32,200)																										
SEER		17.8	19.4	20.2	18.5	18.6	27.4	25.2	22.7	22.0																										
EER		11.1	11.6	12.7	12.5	12.5	16.3	13.2	12.5	12.5																										
HSPF		10.3	10.6	10.3	10.3	10	13.8	13.0	12.5	13																										
AHRI #	AHRI	207776287	207776289	205776148	205776150	205776151	207158009	207158010	207158011	207158012																										
MOP		15					20					15					20																			
Line Size (in.) (mm)		1/4 x 3/8 (6.4 x 9.5)			1/4 x 1/2 (6.4 x 12.7)		1/4 x 3/8 (6.4 x 9.5)			1/4 x 1/2 (6.4 x 12.7)		1/4 x 5/8 (6.4 x 15.9)																								
Max Length (ft.) (m)		65.625 (20)					98.4 (30)					82.015 (25)					98.4 (30)																			
Max Height (ft.) (m)		49.25 (15)					65.625 (20)					65.625 (20)					82.015 (25)																			
Chargeless (ft.) (m)							32.8 (10)					49.2 (15)																								
Add'l Charge (oz./ft.) (g/m)		0.21 (20)					0.22 (20)					0.22 (20)																								
Operating Range	Cooling Operation Range	50 - 115°F (10 - 46°C)					50 - 115°F (10 - 46°C)										50 - 115°F (10 - 46°C)																			
	Cooling with Jumper	14 - 115°F (-10 - 46°C)					14 - 115°F (-10 - 46°C)										14 - 115°F (-10 - 46°C)																			
	Cooling with Air Direction Adjustment Grille	-4 - 115°F (-20 - 46°C)					-4 - 115°F (-20 - 46°C)										-4 - 115°F (-20 - 46°C)																			
	Air Direction Adjust. Grille	KPW937F4			KPW063B4		KPW937F4E			KPW063B4		KPW937F4			KPW063B4		KPW937F4			KPW063B4		KPW082A41			-											
	Heating Operation Range	5 - 65°F (-15 - 18°C)					-13 - 65°F (-25 - 18°C)					-13 - 65°F (-25 - 18°C)					5 - 59.9°F (-15 - 15.5°C)					-13 - 60°F (-25 - 15.5°C)					5 - 59.9°F (-15 - 15.5°C)					5 - 59.9°F (-15 - 15.5°C)				
	Drain Pan Heater	KEH067A41EA			KEH063A4E / KEH063A4EA		KEH067A41EA / KEH067A41EA			KEH063A4E / KEH063A4EA		KEH067A41EA			KEH063A4E / KEH063A4EA		KEH063A4E / KEH063A4EA			KEH063A4E / KEH063A4EA			KEH063A4E / KEH063A4EA			KEH082A41			-							

* CDMQ & FDMQ not compatible with RXMS48LVJU
 ** Compatible with 2MX18AXVJU only

**Daikin *ATMOSPHERA* not available in all markets

Outdoor Unit	2-Port						3-Port			4-Port			5-Port			8-Zone								
	2MX18AXVJU	2MXS18WMVJU9		2MXL18WMVJU9		3MXS24WMVJU9		3MXL24WMVJU9		4MXS36WMVJU9		4MXL36WMVJU9		5MXS48WMVJU9		RMXS48LVJU								
Installation Type	Non-Ducted						Non-Ducted	Ducted	Mixed	Non-Ducted	Ducted	Mixed	Non-Ducted	Ducted	Mixed	Non-Ducted	Ducted	Mixed	Non-Ducted*	Ducted*				
SEER2	17	16.0	14	15.15	16	14	15.2	18	15	16.45	18	14.9	16.45	18.1	14.9	16.5	20	15.9	15.9	20.6	14.5	17.55	18.8	14.1
EER2	10	11.8	8.8	10.3	12	9	10.5	11.7	8.5	10.1	11.7	8.5	10.1	9.2	8	8.6	11.7	9.3	9.3	10.5	8.2	9.35	10.3	9.3
HSPF2	9	8.7	7.7	8.2	8.7	7.7	8.2	9.7	7.8	8.75	9.7	7.8	8.75	9.4	7.8	8.6	9	8.1	8.1	9.3	7.8	8.55	11.3	9.6
AHRI	207216088	210722659	210725095	210800984	210722664	210725100	210800988	210722661	210725097	210800985	210722665	210725101	210800989	210722662	210725098	210800986	210722666	210800990	210725102	210722663	210725099	210800987	5731240	5731241
Line Size & Qty. (in.) (mm)	1/4 x 2, 3/8 x 2						1/4 x 2, 3/8 x 1, 1/2 x 1 (6.4 x 2, 9.5 x 1, 12.7 x 1)						1/4 x 3, 3/8 x 1, 1/2 x 2 (6.4 x 3, 9.5 x 1, 12.7 x 2)						1/4 x 5, 3/8 x 1, 1/2 x 2, 5/8 x 2 (6.4 x 5, 9.5 x 1, 12.7 x 2, 15.9 x 2)		3/8 x 1, 3/4 x 1 (9.5 x 1, 19.1 x 1)			
Max Length (ft.) (m)	98.4 (30)						164 (50)						229.6 (70)						262 (80)		Refer to Engineering Data			
Max Height (ft.) (m)	49.25 (15)						49.25 (15)						49.25 (15)						49.25 (15)		Refer to Engineering Data			
Chargeless (ft.) (m)	98.4 (30)						98.4 (30)						131.6 (40)						131.6 (40)		Refer to Engineering Data			
Add'l Charge (oz/ ft) (g/m)	-						0.21 (20)						0.21 (20)						0.21 (20)		Refer to Engineering Data			
Operating Range Cooling	50 - 115°F (10 - 46°C)						14 - 115°F (-10 - 46°C)						14 - 115°F (-10 - 46°C)						14 - 115°F (-10 - 46°C)		14 - 115°F (-10 - 46°C)			
Operating Range Heating	5 - 65°F (-15 - 15.5°C)						5 - 59.9°F (-15 - 15.5°C)						-13 - 60°F (-25 - 15.5°C)						5 - 59.9°F (-15 - 15.5°C)		-13 - 60°F (-25 - 15.5°C)		5 - 59.9°F (-15 - 15.5°C)	
Air Direction Adjust. Grille	KPW937F4						KPW063B4						KPW063B4						KPW082A41		-			
Drain Pan Heater	KEH067A41E(A)						KEH063A4E / KEH063A4EA						KEH063A4E / KEH063A4EA						KEH063A4E / KEH063A4EA		KEH082A41		-	

Zone	2MX18A (Max: 24k BTU/h)	2MX*18 (Max: 24k BTU/h)	3MX*24 (Max: 39k BTU/h)	4MX*36 (Max: 48k BTU/h)	5MXS48 (Max: 58k BTU/h)
1	07, 09, 12	07, 09, 12	07, 09, 12	07, 09, 12	07, 09, 12
2	07, 09, 12	07, 09, 12, 15	07, 09, 12, 15, 18	07, 09, 12, 15, 18	07, 09, 12, 15, 18
3	-	-	07, 09, 12, 15, 18	07, 09, 12, 15, 18, 24*	07, 09, 12, 15, 18
4	-	-	-	07, 09, 12, 15, 18, 24	07, 09, 12, 15, 18, 24
5	-	-	-	-	07, 09, 12, 15, 18, 24

**24k BTU/h IDU connection only possible with optional 1/2" to 5/8" adaptor (4015875)